

		2900 / 2900V	2910	2930	2950
Dual-WAN		-	V	V	V
VPN	Tunnel	32	32	100	200
	Encryption	H/W DES/3DES S/W MPPE/AES	H/W DES/3DES S/W MPPE/AES	H/W AES/DES/3DES S/W MPPE	H/W AES/DES/3DES S/W MPPE
	Key Hash	S/W MD5/SHA-1	S/W MD5/SHA-1	H/W MD5/SHA-1	H/W MD5/SHA-1
	Key Exchange	Pre-shared Key	Pre-shared Key/CA	Pre-shared Key/CA	Pre-shared Key/CA
VolP	Registrar	0 / 2 dedicated	6	6	-
	ISDN FXS (S0)	-	-	V	-
	ISDN FXO	-	V	V	-
Wireless	Solution	IEEE 802.11b/g	Super G [™]	IEEE 802.11n	Super G [™]
	VLAN	-	V	V	V
	Rate-Control	-	V	V	V
	WDS	- / V	V	V	V
Firewall	Object-Originated	-	V	V	V
	Content Filter	URL / URL&Web	URL&Web	URL&Web	URL&Web
	CSM	IM&P2P blocking	V	V	V
	IP/MAC Binded	MAC Address Filter	V	V	V
Bandwidth	QoS	V	V	V	V
Management	NAT/Bandwidth	-	V	V	V
Others	Ping/Trace Route	_	V	V	V
	Traffic Monitor	-	V	V	V
	WOL	-	V	V	V

DrayTek

Dray Tek

DrayTek



Vigor2910 Product Line

	2910	2910G	2910i	2910V	2910VG	2910VGi
2nd WAN	V	V	V	V	V	V
Wireless	-	Super G^{TM}	-	-	Super G^{TM}	$SuperG^{TM}$
FXS	-	-	-	2	2	2
ISDN	-	-	V	-	-	V
ISDN FXO	-	-	-	-	-	V
ISDN Loop-through	-	-	-	-	-	V



Vigor2910 Product Line









Vigor2910 Product Line

Vigor2910i





- High-integration with 802.11g, VoIP and ISDN
- Configurable 2nd WAN for policy-based Load-Balance and Fail-Over/BoD
- SuperGTM provides up to 108Mbps data rate
- Wireless Security
 - WEP/WPA/WPA2 Encryption, MAC Address Control, Wireless LAN Isolation, Wireless VLAN and 802.1x Authentication
- WDS (Wireless Distribution System), Wireless AP Discovery and Rate Control support



- Two FXS ports with six SIP registrars support
- ISDN BRI interface for VoIP on-net/off-net and loop-through calls
- Supplementary services
 - Call Hold, Call Waiting, Call Transfer, Call Forwarding, DND (Do Not Disturb), Hotline and T.38
- QoS
 - Class-based bandwidth guarantee by user-defined traffic categories
 - 4-level priority for each direction (Inbound/Outbound)
 - Assure bandwidth for own VoIP service



- Bandwidth/NAT session limitation
- Object-Oriented Firewall makes setting of policies easy
- CSM (Content Security Management) allows more precise and efficient access control for IM and P2P applications
- Firewall supports IP Filter, MAC Address Control, DoS/DDoS Protection, Web/URL Content Filter and IM/P2P Blocking
- HTTPS and SSH secure management



- 32 VPN tunnels with MPPE, AES and hardwarebased DES/3DES encryption
- One USB 1.1 host for USB printer
- Automatic ISDN backup when ADSL2+ fails



Vigor2930 Product Line

	2930	2930n	2930Vn	2930VS	2930VSn
2nd WAN	V	V	V	V	V
Wireless	-	802.11n	802.11n	-	802.11n
FXS	-	-	2	2	2
ISDN FXS (S0)	-	-	-		
ISDN FXO	-	-	-	2	2
ISDN Loop-through	-	-	-	Ζ.	2



Vigor2930 Product Line









Vigor2930 Product Line







- High-integration with 802.11n, VoIP and ISDN
- Dual-WAN with policy-based Load-Balance and Fail-Over/BoD
- Wireless Security
 - WEP/WPA/WPA2 Encryption, MAC Address Control, Wireless LAN Isolation, Wireless VLAN and 802.1x Authentication
- WDS (Wireless Distribution System), Wireless AP Discovery and Rate Control support
- Item 100 VPN tunnels with MPPE, AES and hardwarebased DES/3DES encryption



- Six SIP registrars
- Two FXS ports
- One fixed and one configurable ISDN TE/NT ports
- Supplementary services
 - Call Hold, Call Waiting, Call Transfer, Call Forwarding, DND (Do Not Disturb), Hotline and T.38
- QoS
 - Class-based bandwidth guarantee by user-defined traffic categories
 - 4-level priority for each direction (Inbound/Outbound)
 - Assure bandwidth for own VoIP service



- Bandwidth/NAT session limitation
- Object-Oriented Firewall makes setting of policies easy
- CSM (Content Security Management) allows more precise and efficient access control for IM and P2P applications
- Firewall supports IP Filter, MAC Address Control, DoS/DDoS Protection, Web/URL Content Filter and IM/P2P Blocking
- HTTPS and SSH secure management



Vigor2950 Product Line

	2950	2950G	2950i	2950Gi
Dual-WAN	V	V	V	V
Wireless	-	Super G^{TM}	-	Super G^{TM}
ISDN	-	-	V	V



Vigor2950 Product Line







Vigor2950 Product Line







- High-integration with 802.11g and ISDN
- Dual-WAN with policy-based Load-Balance and Fail-Over/BoD
- SuperGTM provides up to 108Mbps data rate
- Wireless Security
 - WEP/WPA/WPA2 Encryption, MAC Address Control, Wireless LAN Isolation, Wireless VLAN and 802.1x Authentication
- WDS (Wireless Distribution System), Wireless AP Discovery and Rate Control support



- CSM (Content Security Management) allows more precise and efficient access control for IM and P2P applications
- Firewall supports IP Filter, MAC Address Control, DoS/DDoS Protection, Web/URL Content Filter and IM/P2P Blocking
- HTTPS and SSH secure management
- 200 VPN tunnels with MPPE and hardware-based AES/DES/3DES encryption



QoS

- Class-based bandwidth guarantee by user-defined traffic categories
- 4-level priority for each direction (Inbound/Outbound)
- Assure bandwidth for own VoIP service
- Bandwidth/NAT session limitation
- Automatic ISDN backup when ADSL2+ fails



