



Model No.	QH-NP7174F-A-F36
OPERATION	
OSD menu	English, Chinese, German, French, Russian, Italian, Spanish optional
Preset position	256 preset positions optional
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	8 tracks, preset, speed and dwell time changeable
Pattern	6 lines (Pan/Tilt/Zoom, Every line can record up to 120 seconds)
Alarm	4 alarm inputs, 2 alarm outputs optional
Password Protection	YES
Temperature Display and Settings	YES (Temperature alarm set, temperature display)
Authority Management	YES
Private masking	24 (Linked Private masking)
Address range	0—255 (Set up by Dip switcher, Firmware)
Communication	RS485 (+/-)
Baud rate	2400/4800/9600/19200
Protocol	Pelco-D, Pelco-P, Ultratrack, Vicon, Dynacolor
Device title	Display on/off
Zoom times	Display on/off
Firmware Update interface	RS485 (+/-)
MECHANICAL	
Pan Range	0°-360° continuously
Pan Speed	0.1~ 240°/s
Tilt Range	0°~ 90° auto flip 180° to continue monitor

Tilt Speed	0.1~ 180°/s
Precision	±0.10°
INFRARED	
IR Distance	150 meters
IR Control	Auto/Manual
IR Driver	PWM
IR Detect Time	2~15s, sync with the camera
IR Light Level	0~30 adjustable
IR Sensitivity	0~30 adjustable
Standby Level	OFF/1~30 adjustable
IR Mode	Auto/Far/Near/Far Near/Close
OTHERS	
Housing	Aluminum alloy, vandal proof housing, Wall mount, Ceiling Mount
Lighting proof	6000V
Protection	IP66
Work Temp	-40°C~ 60°C
Work Humidity	0%~ 90%
Power	AC24V/4A
Weight	4800g
Zoom Lens Option	Sony 36X zoom, D/N 1/4" sony ExViewHAD(color :550TVL,B/W:570TVL), f=3.4-122.4mm(F1.6-4.5), Color:0.07Lux B/W:0.01Lux, IR-CUT, WDR