

# RL-CD-814

Plastic Dome Camera



CE

## Specification Technical:

Model: RL-CD-814 > COLOR

|                         |                         |
|-------------------------|-------------------------|
| Signal System:          | PAL                     |
| Sensor CCD:             | 1/3" Sony Super HAD CCD |
| Horizontal resolution : | 420TV lines             |
| Lens:                   | 3.6 mm                  |
| Minimum Illumination:   | 0 LUX (IR ON)           |
| S/N Ratio:              | More than 52 dB         |
| View Angle:             | 40~87°                  |
| Average life:           | 20000 hours             |
| Video Output:           | 1Vp-p 75Ω .             |
| Connector video :       | BNC                     |
| Operation Temperature:  | -20°C to +50°C          |
| Housing:                | IP65                    |
| Supplied Power:         | 12Vcc (+/-10%);         |
| Dimension:              | 130*130*120 mm          |

### NOTE :

1. Make sure that the power supply is DC 12V(+/-10%).
2. Wrong cable connections will cause malfunction and/or damage the camera.
3. Do not expose the lens directly into sunlight or bright objects, as the CCD can be damaged.
4. Do not expose to extreme hot and cold temperatures.(Recommended operation: -20~50°C)
5. Do not attempt to disassemble or repair the camera yourself. This may damage and void your warranty.