

H.264 Digital Video Recorder

RL-HD-VR-5908H



Product Features

- Real-time monitoring

With composite video signal interface, support TV, VGA, or HDMI output simultaneously.

- Compression processing functions

H.264 video compression standard and G.711 audio compression standards.

- Video features

Supports timer, alarm linkage, motion detection recording mode and also support the SATA HDD and the Local HDD S.M.A.R.T.R technology. Besides, the records support the USB interface to backup and the network backup function

- Records playback function

Support video search by a variety of conditions, to realize the Local and Network playback; Support many channels playback with quick、slow、reverse and frame by frame mode at the same time; The actual time can display when the record playback

- Camera manage and alarm

Support manage the camera remotely: All kinds of alarm device can connect with many channels alarm input interface; Support motion detection、video loss、video shelter alarms; Support the alarm joint and the light control with many channels alarm output

- Communication interface

Support many kinds of backup devices with high speed USB2.0 interface or SATA interface; Support plug and play in all kinds of network with standard Ethernet interface

- Network function

Support the TCP/IP、UDP、RTP/RTSP、DHCP、PPPoE、DDNS、NTP protocol; Support the live monitor、record playback、manage function; Support the direct access from browser with the

built-in WEB Server

SPEC

	Model	HD-VR-5908H
System	CPU	GM8287
	Operating System	Linux
Video	Video Compression	H. 264
	Preview	960H
	Record Resolution	960H
	Playback Resolution	960H
	Synchronous Playback	4*960H
	Video input	8*BNC
	Video output	VGA*1 HDMI*1 V-OUT*1
Audio	Audio Compression	8K*16bit ADPCM
	Audio input	4*RCA
	Audio output	1*RCA
External Alarm	Alarm External	nonsupport
PTZ	485 Port	1
Input Control	Mouse	nonsupport
Storage and Back-up	SATA port	support
	Esata	nonsupport
	DVD-RW driver	1*3TB
External Alarm	Alarm External	nonsupport
PTZ	485 Port	nonsupport
USB	USB 2.0 port	2
power	power	DC12V/2A

consumption	wattage	24W
Remote monitoring	Mobile monitor	iPhone, Android
	Voice talk-back	nonsupport
	Network	1 RJ45 10M/1000M
Other	operating temperature	-20°C~+55°C
	Dimension	250 (W) *40 (H) *230 (D)
	Weight	1.254Kg

Dimension

Application

Applicable to financial services, telecommunications, government, schools, airports, factories, hotels, museums, traffic monitoring, and other places

Picture



Accessory