




Space Dome Camera

Features :


- Sony Super HAD CCD sensor
- Built-in Vari-Focal Lens / Board Lens
- Hi-Res. 550 TVL (for YK-2G83, 2G83VF3/VF9)
- DC or DC/AC Dual voltage



YK-2G49VF3 / 2G83VF3



YK-2G57VF3



YK-3G41VF3/3G43VF3

Model No.	YK-2G49VF3/VF9	YK-2G57VF3/VF9	YK-2G83VF3/VF9	YK-3G41VF3/VF9	YK-3G43VF3/VF9
	YK-2G49 YK-2G59U	YK-2G15 YK-2G43U	YK-2G83	YK-3G41 YK-3G53U	YK-3G43 YK-3G55U
Image Device	1/3" Color Sony Super HAD	1/3" Color Sony Super HAD (Hi-Res.)		1/3" B/W Sony Super HAD	1/3" B/W Sony Super HAD (Hi-Res.)
Picture Elements	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582		EIA:510x492, CCIR:500x582	EIA:768x494, CCIR:752x582
Resolution	380 TVL	470 TVL	550 TVL	420 TVL	600 TVL
Min. Illumination	0.2 Lux / F 2.0	0.4 Lux / F 2.0	0.4 Lux / F 2.0	0.1 Lux / F 2.0	0.2 Lux / F 2.0
S/N Ratio	More than 48dB				
Electronic Shutter	NTSC:1/60~1/100,000, PAL:1/50~1/110,000			EIA:1/60~1/100,000, CCIR:1/50~1/110,000	
Flickerless Mode	On / Off (for VF3,VF9 model)			-	
Gamma	0.45				
Iris Control	DC Drive (for VF3,VF9 model)				
Lens Furnished	VF3 model : Vari-Focal 3.3~12mm / F1.5~360, Wide: 83.9°x61.9°, Tele: 23.91°x17.93° (HxV) VF9 model : Vari-Focal 9.0~22mm / F2.0~360, Wide:29.2°x21.7°, Tele: 13.0°x9.7° (HxV) Other model: Board Lens 3.6mm / F2.0 (option:2.5/4.3/6/8/12/16mm)				
White Balance	Auto			-	
Gain Control	High / Low (for VF3,VF9 model) Auto (for other model)			Auto	
Back Light Comp.	On / Off				
Sync. System	Internal, Line Lock (for U model)				
Video Output	1 Vp-p / 75 Ohms				
Power Supply	U model : DC12V/AC24V Dual Other model: DC12V±10%, DC12V/AC24V Dual (option)				
Power Consumption	2.2W max.	2.9W max.	2.0W max.	1.9W max.	2.0W max.
Operating Temp.	-10°C ~ 50°C				