



4CH/8CH/16CH MPEG4 Network DVR

Features


- Motion Detection recording
- Alarm Input / Output
- System auto detection (NTSC / PAL)
- Max. 60 images per second recording
- 750GB HDD support
- CF card backup
- TCP/IP network connection (option)



RYK-9324N



RYK-9327N



RYK-9326N

Model No.		RYK-9326	RYK-9327	RYK-9324
		RYK-9326N	RYK-9327N	RYK-9324N
Video	Format	NTSC / EIA or PAL / CCIR		
	Compression	MPEG4		
	Input	16 CH, BNC	8 CH, BNC	4 CH, BNC
	Output	1CH BNC, 1CH SPOT BNC		1CH BNC, 1CH VGA (option)
Audio	Input	1CH, RCA		
	Output	2CH, RCA		
Display	Resolution	720x480 (NTSC), 720x576 (PAL)		
	Frame Rate	8CH mode: 240 / 200 IPS (NTSC / PAL) 16CH mode: 120 / 100 IPS (NTSC / PAL)	240 / 200 IPS (NTSC / PAL)	120 / 100 IPS (NTSC / PAL)
	Division	Single, Sequence, Spit (4,9,16)	Single, Sequence, Spit (4,9)	Single, Quad, Sequence
Recording	Resolution	704x240 (NTSC), 704x288 (PAL)		352x240 (NTSC), 352x288 (PAL)
	Frame Rate	Max. 60 / 50 IPS (NTSC / PAL)		
	Quality	High / Medium / Low		
	Mode	Manual / Schedule / Alarm / Motion Detection		
HDD	Basic Storage	1x3.5" IDE HDD (Removable, Max. 750GB)		
Alarm	Input / Output	16 / 1 (NO / NC programmable)	8 / 1 (NO / NC programmable)	4 / 1 (NO / NC programmable)
	Triggered Mode	Motion Detection, Video Loss, Sensor Input		
	Action	Recording, Relay Output, Sound Alert		
Network	Ethernet	10 / 100 BaseT Ethernet (RJ-45) (for RYK-9326N/9327N/9324N)		
	Protocol	TCP/IP, PPPoE, DDNS, SMTP, ICMP, ARP (for RYK-9326N/9327N/9324N)		
Post Alarm		1 ~ 60 sec		
Search Method		By Date, Time		
Motion Detection		Detect area selectable and sensitivity adjustable		
Password Protection		Yes		
Backup Device		CF-Card (ASF File format), VCR		
Power Supply		AC100~240V 50/60 Hz, DC12V / 4.2A		
Weight		3.6 Kg (without HDD)		
Dimensions (WxHxD)		430x70x316 mm		
Operating Environment		30 ~ 80% RH, 5°C ~ 40°C (41°F ~ 104°F)		

■ IPS: Images Per Second