

RYK-2B49, 83, 79/1



20M Cable Management IR Camera

Features

- 420~550 TV Line
- Support AWB, AGC and AES
- Built-in 24 Pieces IR-LED (up to 20M)
- Dual Window Structure
- 3-AXIS Concealed Cable Bracket
- Weatherproofing IP68



Dimension



Specification

Model No.	RYK-2B49L2/1	RYK-2B83L2/1	RYK-2B79L2/1
Image Device	1/3" Color Sony Super HAD II		1/3" Color Sharp
Picture Elements	NTSC:510x492, PAL:500x582		NTSC:768x494, PAL:752x582
Resolution	420 TVL	550 TVL	540TVL
Min. Illumination	0.05 Lux / F1.2 (IR Off)		0.1 Lux / F 1.2 (IR Off)
S/N Ratio	More than 48dB		
Electronic Shutter	NTSC: 1/60~1/100,000, PAL: 1/50~1/100,000		
Gamma	0.45		
Iris Control	Fixed		
Lens Furnished	Board Lens 3.6 mm / F2.0 (Optional: 4.3 / 6 / 12 mm)		
Sync. System	DC12±10%		
Power Supply	Interanl		
Power	IR On	360mA max.	390mA max.
Consumption	IR Off	125mA max.	170mA max.
Operating Temp.	-10°C ~ 50°C		95mA max.

RYK-2B49, 83, 79/7

20M Cable Management IR Camera

Features

- 420~550 TV Line
- Support AWB, AGC and AES
- Built-in 24 Pieces IR-LED (up to 20M)
- Dual Window Structure
- 3-Axis Concealed Cable Bracket
- Weatherproofing IP68



Coming Soon!

Dimension

Coming Soon!

Specification

Model No.	RYK-2B49L2/7	RYK-2B83L2/7	RYK-2B79L2/7
Image Device	1/3" Color Sony Super HAD II		1/3" Color Sharp
Picture Elements	NTSC:510x492, PAL:500x582		NTSC:768x494, PAL:752x582
Resolution	420 TVL	550 TVL	540TVL
Min. Illumination	0.05 Lux / F1.2 (IR Off)		0.01 Lux / F 1.2 (IR Off)
S/N Ratio	More than 48dB		
Electronic Shutter	NTSC: 1/60~1/100,000, PAL: 1/50~1/100,000		
Gamma	0.45		
Iris Control	Fixed		
Lens Furnished	Board Lens 3.6 mm / F2.0 (Optional: 4.3 / 6 / 12 mm)		
Sync. System	Internal		
Power Supply	DC12±10%		
Power	IR On	360mA max.	390mA max.
Consumption	IR Off	125mA max.	170mA max.
Operating Temp.	-10°C ~ 50°C		95mA max.