

H.264 Video Server

Features

- H.264/MJPEG
- Support 2 Way Audio
- Support SD Card for Local Storage & Event Log
- Multiple Event Trigger Management
- Support SDK for SI Integration
- Support PoE(Optional)
- Free Bundle 32 CH Recording Software
- Support 3G Mobile Viewing

H.264 High Performance



▪ RYK-VS340E

- SecuCON Lite - Free Bundle 32 CH Recording Software



▪ RYK-VS310E

Model No.		RYK-VS340E	RYK-VS310E
Video	Format	NTSC / EIA / PAL / CCIR	NTSC / EIA / PAL / CCIR
	Source	4 x BNC	1 x BNC
	Compression	H.264/MJPEG Simultaneously	H.264/MJPEG Simultaneously
	FPS	30FPS@CIF (NTSC) 25FPS@CIF (PAL) 8FPS@D1 (NTSC / PAL)	30/25 FPS@All Resolution (NTSC / PAL)
	Monitor Out	1Vp-p / 75 Ohms	No
Audio	Line In	4CH, RCA Jack	1CH, Phone Jack
	Line Out	1CH, RCA Jack	1CH, Phone Jack
	Direction	2 way Audio	2 way Audio
Storage	SD Card	SDHC SD2.0 up to 32GB	SDHC SD2.0 up to 32GB
Alarm	Alarm In	4 In, Dry Contact N.C./N.O. adjustable by software	1 In, Dry Contact N.C./N.O. adjustable by software
	Alarm Out	4 Relay Out, Dry Contact	1 Out, Dry Contact
Peripheral	Serial Connectors	RS232 / RS485 / RS422 Palco D & Palco P	RS485 Palco D & Palco P
	LED	3 LED (Power LED & 2 Mode Status LED)	3 LED (Power LED & 2 Mode Status LED)
	WDT	Hardware & Software WDT	Hardware & Software WDT
Network	Ethernet	10/100 Base T Ethernet (RJ-45)	10/100 Base T Ethernet (RJ-45)
	Protocol	IPv4, HTTP, FTP,SMTP,UPnP DNS,DDNS,RTSP,RTP,TCP UDP, ICMP, DHCP	IPv4, HTTP, FTP,SMTP,UPnP DNS,DDNS,RTSP,RTP,TCP UDP, ICMP, DHCP
	Auto Reconnect	Yes	Yes
Software	Motion Detection	Yes	Yes
	32 CH	Yes	Yes
SDK		Yes	Yes
Power Supply		DC 12V/PoE	DC 12V/PoE
Power Consumption		7W	4W
Dimensions (WxHxD)		210x44.5x112.3mm	89x31.5x123.2mm
Operating Environment		0%~90% RH, 0°C~50°C (32°F~122°F)	0%~90% RH, 0°C~50°C (32°F~122°F)