



Vigor2200 Series DSL/Cable Routers



Easy Internet Access via broadband technology for SOHO

Share broadband Internet access from Ethernet ADSL modem/Cable modem by NAT Port Forwarding/Opening (by range, port & DMZ)

Protection via Firewall for the attack from the Internet
Call scheduling presets the Internet/ LAN-to-LAN access at certain time or duration

VPN facilities support up to 8 IPSec/3DES/PPTP VPN tunnels simultaneously

Safeguarded remote dial-in/out access via ISDN or Broadband(VPN)

Time-saving E-commerce, Video-on-demand, Interactive learning and online shopping for multiple users

User-friendly Web-based Interface for installation, configuration and management



Features		Vigor2200	Vigor2200X	Vigor2200E
Hardware Interface	LAN	4-port 10/100M BaseTX Switch One 10/100M BaseTX port	---	YES
	WAN	One 10M Base-T port with a RJ-45 connector	YES	YES
	ISDN	Europe DSS1, Germany 1TR6; RJ-45 BRI(S/T)	YES	YES
	Power	AC 16V	YES	YES
WAN Protocol	PPPoE	YES	YES	YES
	DHCP	YES	YES	YES
	PPTP	YES	YES	YES
	Static IP	YES	YES	YES
NAT	Multi-NAT	YES	YES	YES
	DMZ	YES	YES	YES
	Port Redirection	YES	YES	YES
	Open Ports	YES	YES	YES
	Pass-through(VPN, VoIP, Netmeeting, MSN messenger, ICQ, Quake, Startcraft...etc.)	YES	YES	YES
Virtual Private Network	IKE Key Management	YES	YES	YES
	IPSec, PPTP, L2TP, L2TP over IPSec	YES	YES	YES
	3DES, DES and AES encryption	YES	YES	YES
	MPPE encryption for PPTP	YES	YES	YES
	Max to 8 tunnels	YES	YES	YES
	RADIUS support	YES	YES	YES
Firewall Features	Access Control	YES	YES	YES
	IP-based Packet Filtering	YES	YES	YES
	Stateful Packet Inspection	YES	YES	YES
	Denial of Service Prevention	YES	YES	YES
Routing Support	RIPv2	YES	YES	YES
	Configurable Static Route	YES	YES	YES
Network Features	DHCP server/relay	YES	YES	YES
	Dynamic DNS	YES	YES	YES
	Call Scheduling	YES	YES	YES
Management	Web-based user interface	YES	YES	YES
	Telnet remote access support	YES	YES	YES
	TFTP for F/W upgrade/backup	YES	YES	YES
	Built-in Diagnostic Function	YES	YES	YES
	Quick Start Wizard	YES	YES	YES
	Syslog Monitor	YES	YES	YES
Max. Power Consumption	6.4 Watt			
Dimension	L21.8 x W15.8 x H3.6 (cm)			



Applications

Secured Internet Access



Virtual TA



Versatile Management



Dynamic Domain Name Server



Vigorous Broadband Access

DrayTek

Taiwan www.draytek.com.tw
E-mail: info@draytek.com.tw
Tel: +886 3 597 2127 Fax: +886 3 597 2121

