
Online Status

Introduction

The **Online Status** provides some useful information for system information, ISDN, LAN and WAN interface. Also, you could use the status page to get the Internet access status.

Online Status Descriptions

Click **Online Status** to open the Online Status page. In the example, on the following page, the router is working on Dynamic IP mode to access the Internet.

> System Management> Online Status							<<Main Menu	
System Status							System Uptime: 0:1:22	
ISDN Status								
Channel	Active Connection		TX Pkts	TX Rate	RX Pkts	RX Rate	Up Time	AOC
B1	Idle [---]		0	0	0	0	0:0:0	0
B2	Idle [---]		0	0	0	0	0:0:0	0
D	UP							
							>>Drop B1 >> Drop B2	
LAN Status								
	IP Address		TX Packets		RX Packets			
	192.168.1.1		549		451			
WAN Status								
Mode	IP Address		GW IP Addr	172.16.2.1				
DHCP Client	172.16.2.57		TX Packets	TX Rate	RX Packets	RX Rate	Up Time	
			14	74	22	95	0:00:13	
							>>Drop PPPoE or PPTP	

The Online Status page contains three subgroups: System Status, LAN Status and WAN Status.

System Status:

System Uptime: The router's running time. The format is HH:MM:SS where HH means hours, MM means minutes, and SS means seconds.

ISDN Status: (Vigor2200, Vigor2200X and Vigor2200W only)

Active Connection: The ISP, active remote ISDN dial-in user, or LAN-to-LAN connection name and also the IP address for each B channel.

TX Pkts: Total number of transmitted IP packets sent during this connection session.

TX Rate: Transmission rate for outgoing data. The unit is characters per second (cps).

RX Pkts: Total number of received IP packets received during this connection session.

RX Rate: Reception rate for incoming data. The unit is characters per second (cps).

Up Time: Connection time. The format is HH:MM:SS where HH means hours, MM means minutes, and SS means seconds.

Drop B1: Click to disconnect the B1 channel.

Drop B2: Click to disconnect the B2 channel.

LAN Status:

IP Address: IP address of the LAN interface.

TX Packets: Total number of transmitted IP packets sent since the router was powered on.

RX Packets: Total number of received IP packets received since the router was powered on.

WAN Status:

Mode: Indicates which broadband access mode is active. Depending upon the broadband access mode, you may see **Static IP**, **Dynamic IP**, **PPTP**, or **PPPoE**.

GW IP Addr: Indicates the gateway IP address.

IP Address: IP address of the WAN interface.

TX Packets: Total number of transmitted IP packets sent during this connection session.

TX Rate: Transmission rate for outgoing data. The unit is characters per second (cps).

RX Packets: Total number of received IP packets received during this connection session.

RX Rate: Reception rate for incoming data. The unit is characters per second (cps).

Up Time: Connection time. The format is HH:MM:SS where HH means hours, MM means minutes, and SS means seconds.

Drop PPPoE or PPTP: Click the link to disconnect the PPPoE or PPTP connection.